



Mr. Luke Napier
Polymark (GB) Ltd
14 Sopwith Way - Drayton Fields
GB-NN11 8PB DAVEN TRY, NORTHANTS
VERENIGD KONINKRIJK

Your notice of
2013-10-16

Your reference
e-mail

our reference
CR/2392_2013

date
2013-12-23

Certification report

1. Description of the tested article as indicated by the client:

quality name: Embroidered label FR on fabric
 dimension: 5cm x 10cm
 description: fabric : blue Nomex BV185
 label : Polymark Embroidered label FR

2. Executed tests:

tests from EN ISO 14116	requirements	result	pass/fail and level
flame spread on logo after 5*(75°C proc 4.8 + tumble dry (80°C)) ISO15797			
Index 1	No flaming to the top or either side edge No flaming debris No afterglow shall spread in the undamaged area	No flaming to the top or either side edge No flaming debris No afterglow	Pass Index 1
Index 2	No flaming to the top or either side edge No flaming debris No afterglow shall spread in the undamaged area No hole formation	No flaming to the top or either side edge No flaming debris No afterglow No hole formation	Pass Index 2

This report runs to 2 pages and may be reproduced, as long as it is presented in its entire form, without written permission of Centexbel. The results of the analysis cover the received samples. Centexbel is not responsible for the representativeness of the samples.

Centexbel is authorised by decree of the Ministry of Employment and Labour AV/OA235/ST, dated 25/5/94 and identified under the number 0493 by the European Committee.

CENTEXBEL GENT
 Technologiepark 7
 BE-9052 Zwijnaarde (Gent)
 Tel. +32 9 220 41 51
 Fax +32 9 220 49 55
 e-mail gent@centexbel.be

CENTEXBEL BRUSSELS
 Montoyerstraat 24-B2
 BE-1000 Brussels
 Tel. +32 2 287 08 30
 Fax +32 2 230 68 15
 e-mail brussel@centexbel.be

CENTEXBEL VERVIERS
 Avenue du Parc 38
 BE-4650 Herve (Chaineux)
 Tel. +32 87 32 24 30
 Fax +32 87 34 05 18
 e-mail chaineux@centexbel.be



addressee
Polymark (GB) Ltd

our ref.
CR/2392_2013

date
2013-12-23

page number
2

tests from EN ISO 14116	requirements	result	pass/fail and level
Index 3	No flaming to the top or either side edge No flaming debris No afterglow shall spread in the undamaged area No hole formation After flame of each individual specimen $\leq 2s$	No flaming to the top or either side edge No flaming debris No afterglow No hole formation No after flame	Pass Index 3

tests from EN ISO 11611	requirements	result	pass/fail and level
flame spread on logo after 5*(75°C proc 4.8 + tumble dry (80°C)) ISO15797	Mean after flame ($\leq 2s$) Mean afterglow ($\leq 2s$) in the undamaged area No flaming debris No molten debris No flaming to the top or either side edge No hole formation	No after flame No afterglow No flaming debris No molten debris No flaming to the top or either side edge No hole formation	Pass

tests from EN ISO 11612	requirements	result	pass/fail and level
flame spread on logo after 5*(75°C proc 4.8 + tumble dry (80°C)) ISO15797	Mean after flame, ($\leq 2s$) Mean afterglow ($\leq 2s$) in undamaged area No flaming debris No melting or molten debris No flaming to the top or either side edge No hole formation	No after flame No afterglow No flaming debris No molten debris No flaming to the top or either side edge No hole formation	Pass

Detailed results can be found in:

Centexbel: analysis report 13.03627.01 of 2013-09-13

Kristina De Temmerman
By order of Inge De Witte
Certification Manager