

GloDark Embroidered Emblems



Glow in the dark for fun,
or for safety.

FEATURES

- ☑ Photo-luminescent thread.
- ☑ 100% polyester twill fabric.
- ☑ Charted colours.
- ☑ 100% polyester embroidery threads.
- ☑ Up to 15 colours per design.
- ☑ With or without Merrow borders.
- ☑ Low-melt glue options.
- ☑ Velcro® or pressure sensitive backing options.
- ☑ Heat seal or sew-on application.
- ☑ Commercial launderable.
- ☑ Custom design elements.
- ☑ Available accessory options.
- ☑ Low minimum quantities.
- ☑ No artwork or set-up fees.

Embroidered GloDark Emblems are manufactured with 100% polyester twill fabrics and 100% polyester embroidery threads, where at least one of the design colours is stitched with a formulated fluorescent or photo-luminescent thread. The "GloDark" thread emits a glowing, greenish hue in extremely low-light and dark conditions, indoors or outdoors, with only that part of the design visible. Design elements can be embroidery with a combination of standard and GloDark threads, or with GloDark threads only.

Similar to CustomEmbroidered Custom and LowProfile® Emblems, Embroidered GloDark Emblems can be created with up to 15 thread colours per design, and they can be formatted into many different shapes and sizes. The emblems can be finished with or without a Merrow border, and are produced with a choice of low-melt glue, pressure sensitive, Velcro® or non-woven backings. The emblems can be heat sealed or sewn onto a wide variety of garments and uniforms, are removable, and are commercial launderable.

Embroidered GloDark Emblems can be equipped with accessory features such as button loops, butterfly clutch pins and key-rings, for easy attachment, and with the Velcro® or pressure sensitive backing options, the "stick-on and peel-off" capabilities allow for temporary garment embellishment and branding. Other design elements can be introduced to the embroidery, such as watermarks and background stitch patterns. GloDark threads do need to be "re-charged" in full-light conditions.

HEAT SEAL APPLICATION

Low-melt glue
365°F to 385°F (185°C to 196°C).



For complete product details, please visit
www.emblemtex.com/tekspec.

Be identified. Be recognized!

Emblemtex is pleased to offer you service in English or French, Canada's official languages. **This literature is available in French.**
Emblemtex est fière de vous offrir un service en anglais ou en français, langues officielles du Canada. Cette documentation est disponible en français.

The details contained within this document are offered for informational purposes only. Emblemtex declines all responsibility and liability for any errors or omissions that there may be with respect to this information. These details are subject to change without notice. All logo designs herein are registered by their respective companies. It is the responsibility of the purchaser to be aware of Emblemtex's policies in full.