

# UltraTranz™ Garment & Textile Transfers

TekSpec®  
Product technical details



## PRODUCT DETAILS

### Transfer Dimensions:

- **Minimum** transfer size is **0.5" x 0.5"** (1.27cm x 1.27cm).
- **Maximum** transfer size is **12" x 18"** (30.5cm x 45.7cm).

### Design Lettering Dimensions:

The text within a design should not be less than 2mm (0.08") in height. Smaller text may need to be altered to transfer slightly larger.



### Substrate Type:

**100% polyester clear carrier.**

### Design Colours:

UltraTranz™ transfers are produced using four colour process methods, therefore designs can technically have an unlimited range of colours. Colours can also be referenced from the Pantone® matching system.

## ORDERING GUIDELINES

### Artwork & Set-up Fees:

**No fees\*.** Emblemtek will provide artwork on new emblem orders for customer Approval prior to production. There are no artwork or set-up fees when existing, electronic or physical designs or samples are provided to Emblemtek. Artwork fees may apply when designs are created from scratch.

### Order Quantities:

**Minimum 25.** The minimum order quantity is 25 transfers.

### Pre-production Samples:

**Available \$.** Electronic (scan) or physical pre-production samples (single unit) are available for approved designs. Samples fees are applicable, relative to design detail and emblem size. See price guide for more information.

### Pricing:

**Charted & quoted.** Charted pricing is available up to a certain size threshold, with larger quantities and larger transfer sizes custom quoted. See price guide for more information.

### Delivery Times:

Delivery times are relative to order quantity. See price guide for more information.

### Ordering Guidelines:

**Order specifics.** During the design, artwork and ordering processes, there are specific details that we require in order to proceed with your request, such as:

Transfer Type • Design Colours • Dimensions • Quantity • Special Delivery Needs

### Accepted Design / Artwork File Types

The chart below lists the various graphic and design file types that Emblemtek will accept for artwork and production purposes. Certain file types are preferred as noted.

#### Graphic File Types:

- CorelDraw ver.13 / ver.X3 (.cdr) *pref*
- Adobe Illustrator ver.CS3 (.ai) *pref*
- Encapsulated PostScript (.eps) *pref*
- Adobe Portable Document File (.pdf) *pref*
- Joint Photographic Experts Group (.jpg) *pref*
- Portable Network Graphics (.png) *pref*
- Adobe Photoshop ver.CS3 (.psd)
- Corel Photo-Paint ver.13 / ver.X3 (.cpt)
- Targa Bitmap (.tga)
- Tagged Image File Format (.tiff)
- Windows Bitmap (.bmp)
- CompuServe Bitmap (.gif)



To request a quote,  
please visit  
[emblemtek.com/quote](http://emblemtek.com/quote)



To request literature and samples,  
please visit  
[emblemtek.com/samples](http://emblemtek.com/samples)

## APPLICATION &amp; WASH GUIDELINES

## Application Methods

**Heat seal.** UltraTranz™ Garment and Textile Transfers can be heat sealed on to garments and other textile products using a heat seal machine.

TRANSFER TYPE	HEAT SEAL APPLICATION		
UltraTranz™ Plus	320°F to 356°F (160°C to 180°C)	65 to 80 PSI (4.5 to 5.5 Bar)	12 to 15 seconds
UltraTranz™ Flex	284°F to 320°F (140°C to 160°C)	65 to 80 PSI (4.5 to 5.5 Bar)	5 to 10 seconds

These recommended settings are based on manually operated or air operated heat seal machines with top iron heat only.

## Heat Seal Notes &amp; Tips:

Place the garment or textile on the bottom platen of the heat seal machine and ensure that the area that is to be transferred is as flat and smooth as possible. Place the transfer carrier over the area to be transferred and position the transfer so that the design is aligned to the garment or textile as required. Cycle the heat seal machine based on the temperature, pressure and time settings noted above. When the heat seal cycle is complete, remove the transfer carrier slowly from the garment or textile while still warm.

*Due to the diverse nature of fabrics and textiles in the market place, customers are advised to carry out application, wash and any technical tests (including flame retardant) prior to placing orders.*

- **Thicker fabrics**, which may absorb excess heat, may require longer cycle times as charted above.
- **White materials** (knits or blends) may scorch if heat seal temperatures are too high. It is recommended that fabrics be tested first.
- **Pique knit and fleece** materials may be sensitive to heat and pressure, with the possibility of being crushed.
- **Rib-knit and stretch fabrics** may pucker or distort when transfer are heat sealed to them. Transfers may not apply correctly to items such as toques and scarves. It is recommended that these fabrics be tested first.
- **Terry knit materials** such as towels and bathrobes may not provide a smooth enough surface for proper heat seal application.
- **Treated fabrics** finished with coatings, sizing or repellants may not allow for proper heat seal bonding. Items made with leather, suede, nylon, synthetics, nylon-shell, interlinings, rubberized coatings and reflective fabrics, such as jackets and luggage, may react poorly to heat seal temperatures depending on thickness, weave, texture and weight. It is recommended that these fabrics be tested first, with possible heat seal time and temperature adjustments.
- **Caps** can sometimes be difficult to work with for heat seal applications. To achieve a higher potential for heat seal application success on caps, it is recommended that transfers not be greater than 2-1/4" in height and 4" in width.

## Washing &amp; Drying Guidelines

TRANSFER TYPE	WASH TYPE	WASH TEMPERATURE	DRY TYPE
UltraTranz™ Plus	Industrial	Wash in commercial machine in water <b>not exceeding 176°F (80°C)</b>	Tumble dry at medium heat <b>not exceeding 150°F (65°C)</b>
UltraTranz™ Flex	Commercial	Wash in domestic or commercial machine in water <b>not exceeding 140°F (60°C)</b>	Tumble dry at low heat <b>not exceeding 130°F (55°C)</b>



tel: 800 267 9385  
info@emblemtek.com

For complete product details, please visit  
[emblemtek.com/tekspec/](http://emblemtek.com/tekspec/)

**Be identified. Be recognized!**

Emblemtek is pleased to offer you service in English or French, Canada's official languages. This literature is available in French.  
Emblemtek est fière de vous offrir un service en anglais ou en français, langues officielles du Canada. Cette documentation est disponible en français.

It is the responsibility of the purchaser to be aware of Emblemtek's policies in full. All logo designs herein are registered by their respective companies. The details within this document are offered for informational purposes only, and are subject to change without notice. Emblemtek declines all responsibility and liability for any errors or omissions that may exist.

Pantone® is a registered trademark of Pantone Inc.  
Teflon® is a registered trademark of E. I. du Pont de Nemours  
UltraTranz™ and TekSpec® are trademark and registered trademark of Emblemtek Solutions Group Inc.

Copyright © 2023 Emblemtek Solutions Group Inc. rev. 2023-04

